












# HM MASKING TAPES

INFORMATIVE  
DATA SHEET



	 backing weight g/m <sup>2</sup>	 total thickness µm	 adhesion N/cm	 breaking load N/cm	 elongation at break %	 available colours	 organic solvents free	 D.I.Y.	 easy cut
NARMASK HM 320	52	115	> 2,7	> 25	> 6	○	•	•	•
NARMASK HM 330	55	120	> 3,6	> 27	> 8	○ ●	•	•	•

○ white      ● yellow

Updated on 11/2023



NAR S.P.A.  
Legnaro (PADOVA) ITALY  
[www.nar-spa.com](http://www.nar-spa.com)

It is good practice to use the product within 12 months from purchase date (6 months if jumbo roll). The rolls must be kept in their original packing. Keep the product out of the light and protect from direct heat sources. The tape must be kept in a dry place, at humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it. The values in the informative data sheets are the average results of tests made on our standard production and are not legally binding. The aesthetic and technical features may be subject to some changes caused by ageing, even though the quality level of the product is maintained. Nar shall not be liable for direct damages or for any consequence arising from the misuse of the product. We suggest the verification of the product suitability to the specific condition of use. Additional indications are available in the last edition of the booklet "Recommendation regarding choice, storing and use of pressure sensitive tapes" published by Federazione Gomma Plastica.



[www.nar-spa.com/  
technical-notes.html](http://www.nar-spa.com/technical-notes.html)



# NARMASK HM 320

INFORMATIVE  
DATA SHEET



ORGANIC SOLVENTS FREE



D.I.Y.



EASY CUT

MADE IN ITALY

## HM MASKING

### COMPOSITION

BACKING: lightly crepe paper  
ADHESIVE: synthetic rubber / hydrocarbonic resins  
CORE: recycled paper and paperboard

### SUITABLE FOR

Light weight fixing; DIY

### AVAILABLE COLOURS

White

The tape has high conformability, good mechanical resistance and it cuts easily. Practical and economical, it is used for general purpose applications in DIY sector.



BACKING WEIGHT  
52 g/m<sup>2</sup>



ADHESION  
> 2,7 N/cm



BREAKING LOAD  
> 25 N/cm



NAR S.P.A.  
Legnaro (PADOVA)  
ITALY  
[www.nar-spa.com](http://www.nar-spa.com)

Membro di:





# NARMASK HM 330

INFORMATIVE  
DATA SHEET



ORGANIC SOLVENTS FREE



D.I.Y.



EASY CUT

MADE IN ITALY

## HM MASKING

### COMPOSITION

BACKING: lightly crepe paper  
ADHESIVE: synthetic rubber / hydrocarbonic resins  
CORE: recycled paper and paperboard

### SUITABLE FOR

Light weight fixing; DIY

### AVAILABLE COLOURS

White - yellow

The tape has high conformability, good mechanical resistance and it cuts easily. Practical and economical, it is used for general purpose applications in building and DIY sector.



BACKING WEIGHT  
55 g/m<sup>2</sup>



ADHESION  
> 3,6 N/cm



BREAKING LOAD  
> 27 N/cm