













PRINTED TAPES

INFORMATIVE
DATA SHEET



	 backing thickness µm	 total thickness µm	 adhesion N/cm	 breaking load N/cm	 elongation at break %	 available colours	 medium weight packaging	 light weight packaging	 automatic sealing machine	 suitable for low temperatures packaging
POLIPRINT 240	28	47	> 2,0	> 39	> 116	Brown / white / transparent		•	•	•
POLINARPRINT 260	32	51	> 2,0	> 45	> 116	Brown / white / transparent	•		•	•
POLINARPRINT 265	32	51	> 2,0	> 45	> 116	Red / orange / black / yellow / dark blue / green / light blue	•		•	•
NARPRINT 140	33	52	> 1,8	> 45	> 48	Brown / white / transparent	•			
NARPRINT 165	37	56	> 1,8	> 50	> 48	Red / orange / black / white / yellow / green / light blue / dark blue / fluo orange	•			
NARPOUCH 240	28	47	n.r.	> 39	> 116	Transparent				
NARPOUCH 260	32	51	n.r.	> 45	> 116	Transparent				

Updated on 05/2017

It is good practice to use the product within 12 months from purchase date (6 months if jumbo roll). The rolls must be kept in their original packing. Keep the product out of the light and protect from direct heat sources. The tape must be kept in a dry place, at humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it.

The values in the informative data sheets are the average results of tests made on our standard production and are not legally binding. The aesthetic and technical features may be subject to some changes caused by ageing, even though the quality level of the product is maintained. Nar shall not be liable for direct damages or for any consequence arising from the misuse of the product. We suggest the verification of the product suitability to the specific condition of use.

Additional indications are available in the last edition of the booklet "Recommendation regarding choice, storing and use of pressure sensitive tapes" published by Federazione Gomma Plastica.



www.nar-spa.com/technical-notes.html



POLI PRINT 240

INFORMATIVE
DATA SHEET



LIGHT WEIGHT PACKAGING



AUTOMATIC SEALING MACHINE



SUITABLE FOR LOW TEMPERATURES PACKAGING

PRINTED TAPES

COMPOSITION

BACKING: printed or pre-printed biaxially oriented polypropylene film

ADHESIVE: natural rubber / hydrocarbonic resins / solvent

CORE: recycled paper and paperboard

SUITABLE FOR

Hand dispensers and automatic sealing machines; sealing of recycled cardboard boxes

AVAILABLE COLOURS

Brown - white - transparent

The quick adhesion at high and low temperatures on all cardboard, the resistance and brilliance typical of polypropylene films, make it ideal for all applications in the packaging sector.



BACKING THICKNESS
28 μ m



BREAKING LOAD
> 39 N/cm



PRINTED TAPE



POLINAR PRINT 260

INFORMATIVE
DATA SHEET



MEDIUM WEIGHT PACKAGING



AUTOMATIC SEALING MACHINE



SUITABLE FOR LOW TEMPERATURES PACKAGING

PRINTED TAPES

COMPOSITION

BACKING: printed or pre-printed biaxially oriented polypropylene film
ADHESIVE: natural rubber / hydrocarbonic resins / solvent
CORE: recycled paper and paperboard

SUITABLE FOR

Hand dispensers and automatic sealing machines;
sealing of recycled cardboard boxes

AVAILABLE COLOURS

Brown - white - transparent

The quick adhesion at high and low temperatures on all cardboard, the resistance and brilliance typical of polypropylene films, make it ideal for all applications in the packaging sector.



BACKING THICKNESS
32 μ m



BREAKING LOAD
> 45 N/cm



PRINTED TAPE



POLINAR PRINT 265

INFORMATIVE
DATA SHEET



MEDIUM WEIGHT PACKAGING



AUTOMATIC SEALING MACHINE



SUITABLE FOR LOW TEMPERATURES PACKAGING

PRINTED TAPES

COMPOSITION

BACKING: printed and pre-printed biaxially oriented polypropylene film

ADHESIVE: natural rubber / hydrocarbonic resins / solvent

CORE: recycled paper and paperboard

SUITABLE FOR

Hand dispensers and automatic sealing machines;
sealing of recycled cardboard boxes

AVAILABLE COLOURS

Red - orange - black - yellow - dark blue - green - light blue

The quick adhesion at high and low temperatures on all cardboard, the resistance and brilliance typical of polypropylene films, make it ideal for all applications in the packaging sector.



BACKING THICKNESS
32 μm



ADESIVITÀ
> 2.0 N/cm



PRINTED TAPE



NARPRINT 140

INFORMATIVE
DATA SHEET



MEDIUM WEIGHT PACKAGING



HAND DISPENSER



WATER RESISTANT

PRINTED TAPES

COMPOSITION

BACKING: printed or pre-printed polyvinylchloride (PVC) film
ADHESIVE: natural rubber / hydrocarbonic resins / solvent
CORE: recycled paper and paperboard

SUITABLE FOR

Hand dispensers; sealing of recycled cardboard boxes;
flexographic machine print

AVAILABLE COLOURS

Brown - white - transparent

The excellent mechanical characteristics of resistance, plasticity and adhesion, combined with silent unwinding, make this tape suitable for all packaging applications and traditional uses.



SPESSORE SUPPORTO
33 µm



PRINTED TAPE



SILENT
UNWINDING



NARPRINT 165

INFORMATIVE
DATA SHEET



MEDIUM WEIGHT PACKAGING



HAND DISPENSER



WATER RESISTANT

PRINTED TAPES

COMPOSITION

BACKING: printed polyvinylchloride (PVC) film
ADHESIVE: natural rubber / hydrocarbonic resins / solvent
CORE: recycled paper and paperboard

SUITABLE FOR

Hand dispensers; sealing of recycled; cardboard boxes.

AVAILABLE COLOURS

Red - orange - black - white - yellow - green - light blue - dark blue - fluo orange

The excellent mechanical characteristics of resistance, plasticity and adhesion, combined with silent unwinding, make this tape suitable for all packaging applications and traditional uses.



BACKING THICKNESS
37 μ m



PRINTED TAPE



SILENT
UNWINDING

MADE IN ITALY



NARPOUCH 240

INFORMATIVE
DATA SHEET



PRINTED TAPES

COMPOSITION

BACKING: printed biaxially oriented polypropylene film
ADHESIVE: natural rubber / hydrocarbonic resins / solvent
CORE: recycled paper and paperboard

SUITABLE FOR

Documents protection on parcels during shipments

AVAILABLE COLOURS

Transparency

This tape is suitable for the documents protection of a wide range of shipping parcels. The non tack adhesive areas avoid any damaging of the document enclosed. Hand or table dispenser application on the package. The printing and the non adhesive areas are customizable.



BACKING THICKNESS
28 μm



PRINTED TAPE



BREAKING LOAD
> 39 N/cm

 TRANSPARENCY

 WATER PROOF

MADE IN ITALY



NARPOUCH 260

INFORMATIVE
DATA SHEET



PRINTED TAPES

COMPOSITION

BACKING: printed biaxially oriented polypropylene film
ADHESIVE: natural rubber / hydrocarbonic resins / solvent
CORE: recycled paper and paperboard

SUITABLE FOR

Documents protection on parcels during shipments

AVAILABLE COLOURS

Transparency

This tape is suitable for the documents protection of a wide range of shipping parcels. The non tack adhesive areas avoid any damaging of the document enclosed. Hand or table dispenser application on the package. The printing and the non adhesive areas are customizable.



BACKING THICKNESS
32 μ m



PRINTED TAPE



BREAKING LOAD
> 45 N/cm



TRANSPARENCY



WATER PROOF